

# SYNTHETIC DOT 3 BRAKE FLUID

### DESCRIPTION:

**DOT 3 Brake Fluid** is a specially compounded preparation designed solely for use in motor vehicle braking systems. It is for use in all vehicles, where grade DOT 3 is recommended by manufactures. **DOT 3 Brake Fluid** far exceeds DOT 3 and other federal and SAE specifications and standards for motor vehicle brake fluid. Mixes with all other approved brake fluids, and is suitable for use in ATE, Girling, Lockheed and other systems.

### DIRECTIONS FOR USE:

- Follow vehicle manufacturer's recommendations when adding brake fluid.
- Keep brake fluid clean and dry. Contamination with dirt, water, petroleum products or other materials may result in brake faultier or costly repairs.
- Store brake fluid only in its original container. Keep container clean and tightly closed to prevent absorption of moisture.
- Do not refill container and do not use for other liquids.
- Avoid spilling on vehicle finish. If spilled, wipe off immediately with clean cloth.

### APPLICATIONS:

**DOT 3 Brake Fluid** is a DOT 3 motor vehicle brake fluid for disks and drum brakes. It meets Federal Motor Vehicle Safety Standard No. 116, SAE-J-1703 and W-B-680a. It is certified by ABIC Independent Laboratories.

\* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

### TYPICAL TEST DATA

Properties	Results
Specific Gravity	1.03 - 1.04
Reflux Boiling Point, Min. (°F)	450
Wet Boiling Point, Min. (°F)	284
Color	Amber

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.