

FULL SYNTHETIC GLOBAL ATF

DESCRIPTION:

Full Synthetic Global ATF is a full synthetic premium fluid designed for automatic transmissions of all North American, European, and Asian passenger car and commercial vehicles. **Full Synthetic Global ATF** provides exceptional oxidation, wear, frictional stability, sludge and deposit prevention, and anti-shudder properties required in today's high performance transmissions. It is also designed to deliver premium performance in older transmissions.

APPLICATIONS:

Full Synthetic Global ATF high viscosity automatic transmission fluid is suitable for use in Ford, GM, Toyota, and many other OEM applications.

Not recommended for use where Ford Type F/G, DCTs, and CVTs fluid is required.

- See table below for Specific Manufacturer's Applications

* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

TYPICAL TEST DATA

Product Specifications	Results
Specific Gravity @ 60 °F	0.8495
Viscosity, Kinematic cSt at 40°C	30.2
cSt at 100°C	7.0
Viscosity Index	208
Viscosity, Brookfield cP at -40°C	8,376
Flash Point, °F	360
Pour Point, °C (°F)	-54 (-65)
Color	RED

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.

Omni Specialty Packaging

SPECIFIC MANUFACTURER'S APPLICATIONS

<u>SUITABLE FOR USE CLAIMS</u>
Aisin Warner AW-1
Allison C-4
Allison TES-295
Allison TES-389, TES-389B
Audi G 052 162, G 052 990, G 055 025
Audi G 055 005, G 055 162, G 052 540
BMW 7045E, BMW 8072B, LA 2634, LT 71141
BMW 83 22 0 142 516
Chrysler MS-10838 P/N 05142893AA
Chrysler MS-1872, MS-5931, P/N 04883077, MS 9602
DSIH 6p805 (Geely, Ssangyong, Mahindra 6sp)
Ford M
Ford M2C195-A
Ford Part # XL-12
GM AutoTrak II
GM P/N 12345866 (GM 9985835)
GM P/N 89021184, P/N 1052884 (GM 9985010)
GM-IID, IIIG, IIIH
Honda ATF Z-1
Honda DW-1
Hyundai NWS-9638
Hyundai/KIA PSF-3
Hyundai/Kia SP-II, SP-III, JWS 3314, JWS 3317
Hyundai/Kia SP-IV, SPH-IV, SP-IV RR
IdemitsuK17 (JATCO)
JASO 1-A
JASO 1-A-LV
JWS 3309 (Aisin Warner)
JWS 3324
Kia Red-1
MAN 339 Type Z-1
MAN 339F, 339 Type V-1
Mazda ATF-M III, ATF-MV
Mercedes GL-450 (ATF 3403)
Mercedes-Benz 236.1, 236.2, 236.3, 236.6, 236.7, 236.9, 236.11, 236.81
Mercedes-Benz 236.12, 236.14, 236.15
Mercedes-Benz 236.3 (P/N 000 989 88 03)
Mercedes-Benz 236.41
Mercedes-Benz 236.91

Omni Specialty Packaging

Mercedes-Benz; MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.9, 236.10 (NAG 1/ Shell 3403), 236.11, 236.81
Mitsubishi ATF-J3, ATF-PA
Mitsubishi PS fluid, Diamond SP-III
Mitsubishi SP-II, SP-III, DiaqueenATF J2
Mitsubishi SP-IV
Nissan 402, Nissan Matic-D, J, K
Nissan MaticS, MaticW
Nissan PSF-II
North American models (DEXRON VI, MERCON LV)
Other North American high viscosity ATF (MERCON V, ATF+4)
PSA AL-4
Renault DP-0
Saab 93 165 147
Saab P/N 45 30 09 800
Subaru ATF, ATF-HP
Subaru P/N K0209A0080
Suzuki 3314, 3317
Texaco N402 (JATCO), ETL-7045E (BMW 7045E), ETL-8072B (BMW 5 Sp)
Toyota PSF Type EH P/N 008886-01
Toyota T, T-II, T-III, T-IV
Toyota WS (JWS 3324)
VoithH55.6335
Volvo 4speed (P/N 1161621)
Volvo 5/6 speed (P/N 1161540/1161640)
Volvo 6 speed MY 2011-2013 (P/N 31256774 or 31256675)
Volvo 97340, 97341
VW G 052 162, G 052 990, G 055 025
VW G 052 540, G 055 005, G 055 162
ZF 6 Speed (S671 090 255)
ZF TE-ML 03D, 04D, 05L,16L, 17C
ZF TE-ML 09
ZF TE-ML 11(3/4/5 speed)
ZF TE-ML 14A
ZF TE-ML 21L

* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.